

COF Series

Specification



DF20

24V-12mm





【General description】

- Light line and dot-free with big emitting angle
- CRI>90,2000LM/M
- Easy to install and maintain
- Double row light belt, can be used with profiles
- With life span over 84000H
- Ta: -25-40°C; Tc: 75°C(max)
- UL/UACK/CE/ROHS/REACH certification



【Dimension】


- | | |
|--|--|
| Input voltage: DC24V | Max.length: 5000mm(16.4') |
| CRI: 90 | Cutting unit: 14.7mm(0.58") |
| Max.power: 22W(1m) | LED pitch: / |
| Power range: 18~22W(1m) | Min. bend diameter: Φ 60mm(2.36") |
| Rated current: 0.83A(1m) | Mounting: 3M tape |
| Typical Power: 20W(1m) | Copper foil: 3oz |
| tape IP: IP20 | |
| On-off times: 10000 (test times) | |
| Warranty: 7 years indoor / 5 years outdoor | |




【Photo-electric Parameters】

CRI	Color	CCT	Lumen(lm/m)	Lumen(lm/ft)	lm/W	ErP 2019
Ra>90	SW	2700K	1630	536	83	G
Ra>90	WW	3000K	1720	536	87	G
Ra>90	PW	3500K	1720	536	87	G
Ra>90	NW	4000K	2095	557	105	G
Ra>90	W	6500K	1890	557	96	G

- 1.The tolerance of output data can be vary up to 10%.
- 2.the output data tested according to IES TM-30-15.
- 3.the output data is based on IP20/1merter , data of 5m in only for reference.
- 4.IP protection process leads changes to size, CCT and luminous flux.




【Electronic & output data】


IP Process	Picture	Picture description	Size	optional CCT/color for finished product	lumen output rate
NO	 NO/IP20	No proof	12mm*1.6mm	2700K/3000K/3500K/4000K/6500K	100%

【Packing】

Colors brand package



General customized package



IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (cm)
NO	5000*12*1.6	5	300	0.17	10.2	11.2	41*41*26

Remark: data with 10% tolerance

· Engineering packaging of NO(IP20).



IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (cm)
NO	50000*8*1.5	50	650	1.7	22.1	23.1	41*41*26

Remark: data with 10% tolerance

【Precautions】

- Please drive the led strip with 24VDC isolated power, and the ripple of the constant voltage source should be less than 5%.
- Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.
- Do not fold it in case any damage of LED beads.
- Do not pull the power wire hard to ensure the longevity. Any Crash may damage the LED light is prohibited.
- Please make sure the wire is connected to the anode and cathode correctly. The power output should be consistent with the voltage of the strip to avoid damage.
- LED lights should be stored in dry, sealed environment. Please only unpack it before usage. Ambient temperature: -25℃~40℃. Storage temperature: 0℃~60℃. Please use the strips without waterproof within indoor environment with humidity less than 70%.
- Please be careful during operation. Do not touch the AC power supply in case of electric shock.
- Please leave at least 20% power for the power supply during using to ensure there is enough power supply to drive the product.
- Do not use any acid or alkaline adhesives to fix the product (e.g.: glass cement).
- Do not scratch the product when IP process of the product is NA. Ultraviolet rays will damage the nano-layers on the product and seriously affect the life of the product.